

XP-002389200

Best Available C

Best Available Copy

1/1 - (C) EPODOC / EPO
AN - CN-97101189-A
AP - CN19970101189 19970318
DT - I
EC - C04B40/00D4
SCI - C04B40/00D4
FAMN- 5165568
IC - (A)

C04B22/00
- (C)
C04B22/00; C04B18/08; C04B24/00
IN - (A C)
TANG MING [CN]; LI ZHIJIAN [CN]
PA - (A)
SHENYANG CONSTRUCTION ENGINEER [CN]
- (C)
SHENYANG BUILDING ENGINEERING [CN]

PN - CN1193616 A 19980923
PR - CN19970101189 19970318
LA - en

UNAP- 97101189

UNIN- MING TANG; ZHIJIAN LI

UNPA- SHENYANG CONSTRUCTION ENGINEERING COLLEGE; SHENYANG BUILDING
ENGINEERING COLLEGE

UNPN- CN 1193616 A
- CN 1061328 C

XEC - C04B-040/00D004

XIC - C04B-022/00; C04B-040/00; C04B-018/08; C04B-024/00

AB - (A)

A process for preparing additives of concrete with ultrafine powdered coal ash includes such steps as grinding powdered coal ash its specific surface area is not less than 1 sq.m/g and mixing naphthalene water-reducing agent, wood calcium and ultrafine powdered coal ash in ratio of 1 : (0.2-0.5) : (8-25) to obtain pumping agent of concrete, or mixing naphthalene water-reducing agent with the powdered coal ash in ratio of 1 : (8-25) to obtain additive of high-strength concrete, or mixing alumina, MC, water-reducing agent and ultrafine powdered coal ash in ratio of 1 : (3-5) : (3-5) : (20-50) to obtain water-proofing agent.

ICAI- (A C)
C04B40/00

ICCI- (A C)
C04B40/00

INW - (A C)
TANG MING [CN]; LI ZHIJIAN [CN]

NPR - 1

OPD - 1997-03-18

PAW - (A)
SHENYANG CONSTRUCTION ENGINEER [CN]
- (C)
SHENYANG BUILDING ENGINEERING [CN]

PD - 1998-09-23